

Unit 6 Oakdale Trading Estate Ham Lane Kingswinford DY6 7JH

Telephone Number: 01562 755884 Emergency Number: 07785 337988

Registered No: 8088650 info@chemi-kal.co.uk

Section 1: Identification of the substance/mixture

and of the company/undertaking

Version 3: 01/11/2021 1.1. Product identifier

Product name:

FOAMBRITE (Acid based foam sanitiser)

Formulated for use in the food industry

Product code:

FOAM

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet Company name: Worcestershire Chemicals Ltd

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP:

Aquatic Chronic 3: H412; Skin Corr. 1A: H314

Most important adverse effects: Causes severe skin burns and eye damage.

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements:

H314: Causes severe skin burns and eye damage.

H412: Harmful to aquatic life with long lasting effects.

Signal words:

Danger

Hazard pictograms:

GHS05: Corrosion



Precautionary statements:

P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards

PBT:

This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

ORTHOPHOSPHORIC ACIDEINECSCAS

PBT / WEL

CLP Classification

Percent

231-633-2

7664-38-2

-

Skin Corr. 1B: H314

10-30%

DBS ACID

-

Acute Tox. 4: H302; Skin Corr. 1A:

H314; Eye Dam. 1: H318; Aquatic

Chronic 3: H412

10-30%

PROPAN-2-OL

200-661-7

67-63-0

-

Flam Liq. 2: H225; Eye Irrit. 2: H319;

STOT SE 3: H336<1%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact:

Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still on skin.

Transfer to hospital if there are burns or symptoms of poisoning.

Eve contact:

Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination. Ingestion:

Wash out mouth with water. Do not induce vomiting.

Give 1 cup of water to drink every 10 minutes. If unconscious, check for breathing and apply artificial respiration if necessary.

If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.

Inhalation:

Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact:

Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact:

Corneal burns may occur. May cause permanent damage

Ingestion:

Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

Inhalation:

There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

Delayed / immediate effects:

Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed Immediate / special treatment:

Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media:

Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Corrosive.

5.3. Advice for fire-fighters

Advice for fire-fighters:

Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures Personal precautions:

Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions:

Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures:

Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections:

Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements:

Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions:

Store in a cool, well-ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s):

No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

ORTHOPHOSPHORIC ACID...100% Respirable dust

Workplace exposure limits:

State

8 hour TWA

15 min. STEL

8 hour TWA

15 min. STEL UK 1 mg/m3 2 mg/m3 PROPAN-2-OL UK 999 mg/m3 1250 mg/m3 **DNEL/PNEC Values** DNEL / PNEC No data available. 8.2. Exposure controls Engineering measures: Ensure there is sufficient ventilation of the area. Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. Hand protection: Impermeable gloves. Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand. Skin protection: Impermeable protective clothing. Section 9: Physical and chemical properties 9.1. Information on basic physical and chemical properties State: Liquid Colour: Red Odour: Barely perceptible odour Evaporation rate: Negligible Solubility in water: Miscible in all proportions Viscosity: Highly viscous Boiling point/ range°C: >35 Flash point°C: >93pH: <2

9.2. Other information

Other information:

No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions:

Hazardous reactions will not occur under normal transport or storage conditions. Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid Conditions to avoid: Heat.

10.5. Incompatible materials Materials to avoid: Bases.

10.6. Hazardous decomposition products

Haz. decomp products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

ORTHOPHOSPHORIC ACID...100%

ORL

RAT

LD50

1530mg/kg

PROPAN-2-OL

IVN

RAT

LD50

1088mg/kg

ORL

MUS

LD50

3600mg/kg

ORL

 RAT

LD50

5045mg/kg

SCU

MUS

LDLO

6gm/kg

Relevant hazards for substance:

Hazard

Route

Basis

Skin corrosion/irritation

DRM

Hazardous: calculated

Serious eye damage/irritation

OPT

Hazardous: calculated

Symptoms / routes of exposure

Skin contact:

Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact:

Corneal burns may occur. May cause permanent damage

.

Ingestion:

Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

Inhalation:

There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

Delayed / immediate effects:

Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity Ecotoxicity values:

No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential:

No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification:

This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations:

Transfer to a suitable container and arrange for collection by specialised disposal company.

NB:

The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number UN number:

UN1760

14.2. UN proper shipping name

Shipping name:

CORROSIVE LIQUID, N.O.S.

14.3. Transport hazard class(es)

Transport class: 8

14.4. Packing group

Packing group: II

14.5. Environmental hazards

Environmentally hazardous:

No

Marine pollutant:

No

14.6. Special precautions for user

Special precautions:

No special precautions.

Tunnel code:

E

Transport category:

1

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Specific regulations:

Not applicable.

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information:

This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3:

H225: Highly flammable liquid and vapour.

H302: Harmful if swallowed.

H314: Causes severe skin burns and eye damage.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer:

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.